


JOPAL® Butyl Sealant Tape

High Performance Butyl Sealing Tape



PRODUCT DESCRIPTION

JOPAL® Butyl Sealant Tape, high-performance butyl rubber sealing tape designed to provide long-lasting waterproof and airtight sealing for roofing, wall cladding, glazing, and general construction applications. The tape forms a permanent seal under compression and remains flexible over a wide temperature range.

TYPICAL APPLICATIONS / KEY FEATURES

- Roofing side lap joints
 - Wall cladding lap joints
 - Sandwich panel joints
 - Metal flashing joints
 - Roof penetrations and fastener sealing
 - HVAC duct sealing
 - Glazing and façade applications
- High-performance butyl rubber compound
 - Excellent waterproof and airtight sealing
 - Cold applied, no heating required
 - Strong adhesion by compression
 - Self-amalgamating seal
 - Flexible over a wide temperature range
 - Solvent-free
 - Easy release liner removal

SIZE RANGE

Art. Code	Thickness (mm)	Width (mm)	Length (m)	Shape
222495192	2.40	9.5	19	Rectangular
223012152	3.00	12.0	15	Rectangular
224763122	4.76	6.35	12	Rectangular
224722122	4.76	22.2	12	U-Shape

TECHNICAL DATA

General Technical Data		
Property	Unit	Value
Material	—	Butyl Rubber
Colour	—	Grey / Black
Solids Content	%	> 99
Adhesion Type	—	Compression Seal
180° Peel Adhesion	N/cm	7
Probe Tack	N	3.5
Compression @ 20% (5°C)	N/mm²	0.8
Application Temperature	°C	+5 to +40
Service Temperature	°C	-30 to +90
VOC Content	g/l	1.5

INSTALLATION GUIDELINES

Surface Preparation — Ensure all contact surfaces are clean, dry, dust-free, and free from oil, grease, loose particles, or moisture before application.
Tape Application — Apply the tape continuously without gaps and compress firmly between the mating surfaces to achieve the required waterproof and airtight seal.
Final Assembly — Do not stretch the tape during installation. Apply uniform pressure over the entire joint to ensure full contact and optimum sealing performance.

STORAGE & SHELF LIFE

Store in the original unopened packaging in a cool, dry, well-ventilated area between +5°C and +30°C, away from direct sunlight and heat sources.
Avoid prolonged exposure to temperatures above 50°C.
Shelf Life: 24 months from the date of manufacture when stored under recommended conditions.

IMPORTANT NOTES

Apply only to clean, dry surfaces.
Sealing performance is achieved by compression after assembly.
For best results, install within the recommended application temperature range.